


Model		12V60W	24V60W
Output	DC Voltage	12V±0.5VDC	24V±0.5VDC
	Rated power	60W	60W
	Current range	5A±1%	2.5A±1%
Input	AC Voltage	90V-250VAC	
	Frequency	50/60Hz	
	AC current	0.52A	
Protection	Overload	100%overloading	
	Short circuit	Auto recovery	
	Over voltage	±255V	
	Over temperature	±80°C	
Others	Waterproof rate	IP67	
	Cooling	by convection	
	Efficiency	> 80%	
	Housing materials	Aluminum	
	Dimension(mm)	155(L)*44(W)*21(H)	
Weight	0.215kg		

ULTRA THIN WATERPROOF POWER SUPPLY

Features:

- IP67 outdoor waterproof device design
- Protection: overvoltage, overload, short circuit
- Organic glue filling, waterproof and moisture-proof
- Energy saving, low consumption and long service life
- The products have passed CE, RoHS, FCC and other certifications
- All aluminum profile shell
- 100% full load aging
- 3-year warranty



Fully sealed glue filling process, waterproof and dustproof



Waterproof led power supply Indoor and Outdoor Use



Widely Use

Flicker-Free For LED Strip Lights, LED Landscape Lights, Pool Lights, Outdoor LED Signs, Modules, Bar Counter Lights, Wine Cabinet Lights, and Other DC 12V LED Product.



LED Module



Camera DC12V



LED Strip Light



LED Light Bulb




LED Display



Spotlight

Dimensions

Unit:mm



AC INPUT
AC (+) (Brown)
AC (-) (Blue)
PE (Green/Yellow)

DC OUTPUT
+12V (Red)
-12V (Black)

Others

DIMENSION	155*44*21mm(L*W*H)
NET WEIGHT	0.215kg/pcs
CARTON SIZE	41.8*25.8*15(cm)
CARTON QUANTITY	40PCS/Carton
PLS WEIGHT	9.10kg/Carton